

# Model TAURUS

## Technical Data

Operating voltage:	85...264VAC / 50Hz...60Hz
Standby:	18 Watts / 80 mA
Rated Power:	91 Watts / 400 mA (max.)
Dimensions (incl. format slide unit):	1110 (max.) x 370 x 370 mm (l x w x h)
Weight:	25.6 kg
Piling-Option:	standard (for stacked and nested envelopes!)
Automatic Start/Stop:	standard on models TAURUS IR/IRC
Counter (integrated):	standard on models TAURUS C/IRC
Length of receiving tray:	382 mm (standard)
Max. width of envelope :	250 mm (B5/B4, B6/5)
Max. thickness of package*:	16 mm
Max. sealing capacity (C5, C5/6):	18'000 envelopes per hour
Power cable length (fixed):	2 meters
Area of use:	according to EU-Norms
Licensing:	CE
Product warranty:	2 years
Accessories (incl.):	Cover, suction rubber pear, replacement fuse, instruction manual

\* Position of bassin two-stage adjustable for envelopes from 0...8mm and 8...16mm. The contents of the envelope in the case of letter thicknesses > 8 mm must be homogeneous, i.e. the max. deviation within the envelope may not exceed 1 mm. Folded letters should be folded as flat as possible!

In the interest of further technical development, any design and technical modifications to the Envelope Sealing Machine are reserved.



### MAAG MERCURE AG

Mail Processing Machines  
Webereistrasse 59  
CH-8134 Adliswil  
Tel. +41 (0)44 710 40 41  
info@maag-mercure.ch  
www.maag-mercure.swiss